



Part Number	(mm)	Resistance at 25° C (Ohms)	Tolerance		I _{max} (Amps)	R _I max (Ohms)	Max. "D" (mm)	Max "T" (mm)	Lead Space (mm)	Lead Diameter (mm)
			min.	max						
JNR08S050M	8	5.0	4.00	6.00	3.0	0.200	10	3.73	5.0	0.6
JNR08S060L		6.0	5.10	6.90	3.0	0.210		3.87		
JNR08S080L		8.0	6.80	9.20	3.0	0.400		4.16		
JNR08S100L		10.0	8.50	11.50	3.0	0.420		4.46		
JNR08S150L		15.0	12.75	17.25	2.0	0.643		5.18		
JNR10S030M	10	3.0	2.40	3.60	5.0	0.130	13	3.75	5.0 OR 7.5	0.8
JNR10S040M		4.0	3.20	4.80	4.0	0.150		4.00		
JNR10S050M		5.0	4.00	6.00	4.0	0.155		4.25		
JNR10S060L		6.0	5.10	6.90	3.0	0.168		4.50		
JNR10S070L		7.0	5.95	8.05	3.0	0.182		4.75		
JNR10S080L		8.0	6.80	9.20	3.0	0.240		5.00		
JNR10S100L		10.0	8.50	11.50	3.0	0.290		5.50		
JNR10S120L		12.0	10.20	13.80	2.0	0.500		3.80		
JNR10S160L		16.0	13.60	18.40	2.0	0.520		4.07		
JNR10S200L		20.0	17.00	23.00	2.0	0.500		4.33		
JNR10S250L	25.0	21.25	28.75	2.0	0.500	4.67				
JNR10S500L	50.0	42.50	57.50	2.0	1.01	3.75				
JNR10S800L	80.0	68.00	92.00	1.0	1.70	4.20				
JNR10S121L	10	120.0	102.00	138.00	1.0	2.200	4.80	7.5 OR 9.5	0.8	
JNR13S2R5M	13	2.5	2.00	3.00	6.0	0.098	4.09			
JNR13S050M		5.0	4.00	6.00	5.0	0.151	5.17			
JNR13S060L		6.0	5.10	6.90	5.0	0.165	5.60			
JNR13S070L		7.0	5.95	8.05	4.0	0.182	6.04			
JNR13S080L		8.0	6.80	9.20	4.0	0.204	3.94			
JNR13S100L	13	10.0	8.50	11.50	4.0	0.211	4.17			
JNR13S120L		12.0	10.20	13.80	3.0	0.250	4.41			
JNR13S160L		16.0	13.60	18.40	3.0	0.367	4.87			
JNR13S200L		20.0	17.00	23.00	3.0	0.382	5.34			
JNR13S250L		25.0	21.25	28.75	2.0	0.411	5.93			
JNR15S1R3M	15	1.3	1.04	1.56	8.0	0.049	18	3.78	7.5 OR 9.5	0.8
JNR15S2R5M		2.5	2.00	2.00	8.0	0.064		4.50		
JNR15S030M		3.0	2.40	3.60	7.0	0.076		3.50		
JNR15S040M		4.0	3.20	4.80	6.0	0.100		3.50		
JNR15S050M		5.0	4.00	6.00	6.0	0.116		3.81		
JNR15S060L		6.0	5.10	6.90	5.0	0.159		3.97		
JNR15S070L		7.0	5.95	8.05	5.0	0.165		4.13		
JNR15S080L		8.0	6.80	9.20	5.0	0.169		4.29		
JNR15S100L		10.0	8.50	11.50	5.0	0.178		4.62		
JNR15S120L		12.0	10.20	13.80	4.0	0.247		3.50		
JNR15S150L	15.0	12.75	17.25	4.0	0.254	3.50				
JNR15S160L	16.0	13.60	18.40	4.0	0.274	3.50				
JNR15S200L	15	20.0	17.00	23.00	4.0	0.290	3.50			
JNR15S250L		25.0	21.25	28.75	3.0	0.410	3.91			
JNR15S400L		40.0	34.00	46.00	3.0	0.470	4.46			
JNR15S470L		47.0	39.95	54.05	3.0	0.541	4.71			
JNR15S800L		80.0	68.00	92.00	2.5	0.725	4.82			
JNR15S121L	120.0	102.00	138.00	2.0	1.136	5.73				
JNR15S221L	15	220.0	187.00	253.00	1.0	2.501	7.00	7.5 OR 10.0	0.8	
JNR20S0R7M	20	0.7	0.56	0.84	12.0	0.032	3.77			
JNR20S1R3M		1.3	1.04	1.56	11.0	0.068	4.44			
JNR20S2R5M		2.5	2.00	3.00	10.0	0.083	5.77			
JNR20S050M		5.0	4.00	6.00	7.0	0.108	3.75			
JNR20S060L		6.0	5.10	6.90	6.0	0.120	4.49			
JNR20S100L	20	10.0	8.50	11.50	6.0	0.136	3.67			
JNR20S120L		12.0	10.20	13.80	5.0	0.210	3.81			
JNR20S121L		12.0	12.00	13.80	2.0	1.205	7.00			